



Cat.	Mod.	 Lavoro	 Ingombro		 HP min - max	 Kg	 Categoria 3° punto	 540° Giri rotore	 1000° Giri rotore	 Numero cinghie	 931060004	 931040003	 931060002	 931060001	 931040013	 931060005	 931040018 (x2) 931990016	 Diametro del rotore	 Diametro del rullo	 Ruote anteriori fisse in ferro	 Ruote posteriori girevoli in gomma	 Kit tabelle stradali
MFW	MFW 160	1600	2000	-	90-180	1320	2°	1750	-	6	-	-	28	-	-	-	-	194	273	-	-	○
	MFW 180	1800	2200	-	95-180	1480	2°	1750	-	6	-	-	32	-	-	-	-	194	273	-	-	○
	MFW 200	2000	2400	-	100-180	1640	2°	1750	-	6	-	-	36	-	-	-	-	194	273	-	-	○
	MFW 220	2200	2600	-	105-180	1800	2°	1750	-	6	-	-	40	-	-	-	-	194	273	-	-	○
MFW DT	MFW 180 DT	1800	2200	-	100-250	1400	2°	-	1818	6+6	-	-	32	-	-	-	-	194	273	-	-	○
	MFW 200 DT	2000	2400	-	110-250	1565	2°	-	1818	6+6	-	-	36	-	-	-	-	194	273	-	-	○
	MFW 220 DT	2200	2600	-	120-250	1730	2°	-	1818	6+6	-	-	40	-	-	-	-	194	273	-	-	○