



Cat.	Mod.	 Lavoro mm	 Ingombro mm	 HP min - max	 Kg	 Categoria 3° punto	 Giri rotore 540°	 Numero cinghie								 Diametro del rotore	 Diametro del rullo	 Kit tabelle stradali
DSK	DSK 120	1200	1340	30 - 80	380	2°	2590	3	14	40	20	-	-	-	-	130	114	○
	DSK 140	1400	1540	30 - 80	410	2°	2590	3	16	48	24	-	-	-	-	130	114	○
	DSK 160	1600	1740	35 - 80	450	2°	2590	4	18	56	28	-	-	-	-	130	114	○
	DSK 180	1800	1940	40 - 80	480	2°	2590	4	20	60	30	-	-	-	-	130	114	○
DSKE	DSKE 120	1200	1550	30 - 80	400	2°	2590	3	14	40	20	-	-	-	-	130	114	○
	DSKE 140	1400	1750	30 - 80	430	2°	2590	3	16	48	24	-	-	-	-	130	114	○
	DSKE 160	1600	1950	35 - 80	470	2°	2590	4	18	56	28	-	-	-	-	130	114	○
	DSKE 180	1800	2150	40 - 80	500	2°	2590	4	20	60	30	-	-	-	-	130	114	○
LG2	LG2 120	1200	1390	35 - 100	570	2°	2280	3	-	-	22	10	28	-	-	150	154	○
	LG2 140	1400	1590	40 - 100	590	2°	2280	3	-	-	26	12	32	-	-	150	154	○
	LG2 160	1600	1790	40 - 100	610	2°	2280	4	-	-	30	14	36	-	-	150	154	○
	LG2 180	1800	1990	50 - 100	640	2°	2280	4	-	-	34	16	40	-	-	150	154	○
	LG2 200	2000	2190	50 - 100	700	2°	2280	4	-	-	38	18	44	-	-	150	154	○
LGE2	LGE2 120	1200	1620	35 - 100	590	2°	2280	3	-	-	22	10	28	-	-	150	154	○
	LGE2 140	1400	1820	40 - 100	610	2°	2280	3	-	-	26	12	32	-	-	150	154	○
	LGE2 160	1600	2020	40 - 100	630	2°	2280	4	-	-	30	14	36	-	-	150	154	○
	LGE2 180	1800	2220	50 - 100	660	2°	2280	4	-	-	34	16	40	-	-	150	154	○
	LGE2 200	2000	2420	50 - 100	720	2°	2280	4	-	-	38	18	44	-	-	150	154	○
SG2	SG2 160	1600	1790	50 - 120	780	2°	2280	4	-	-	-	-	-	14	28 + 14	160	154	○
	SG2 180	1800	1990	50 - 120	840	2°	2280	4	-	-	-	-	-	16	32 + 16	160	154	○
	SG2 200	2000	2190	60 - 120	870	2°	2280	5	-	-	-	-	-	18	36 + 18	160	154	○
	SG2 220	2200	2390	60 - 120	900	2°	2280	5	-	-	-	-	-	20	40 + 20	160	154	○
SGR2	SGR2 220	2200	2390	70 - 200	980	3°	2360	5	-	-	-	-	-	20	40 + 20	160	154	○
	SGR2 250	2500	2690	80 - 200	1100	3°	2360	5	-	-	-	-	-	22	44 + 22	160	154	○
SGE2	SGE2 160	1600	2080	50 - 120	800	2°	2280	4	-	-	-	-	-	14	28 + 14	160	154	○
	SGE2 180	1800	2280	50 - 120	860	2°	2280	4	-	-	-	-	-	16	32 + 16	160	154	○
	SGE2 200	2000	2480	60 - 120	890	2°	2280	5	-	-	-	-	-	18	36 + 18	160	154	○
	SGE2 220	2200	2680	60 - 120	920	2°	2280	5	-	-	-	-	-	20	40 + 20	160	154	○
SGRE2	SGRE2 180	1800	2280	70 - 120	950	3°	2360	5	-	-	-	-	-	16	32 + 16	160	154	○
	SGRE2 200	2000	2480	70 - 120	980	3°	2360	5	-	-	-	-	-	18	36 + 18	160	154	○
	SGRE2 220	2200	2680	70 - 200	1010	3°	2360	5	-	-	-	-	-	20	40 + 20	160	154	○
	SGRE2 250	2500	2980	80 - 200	1130	3°	2360	5	-	-	-	-	-	22	44 + 22	160	154	○